
















Rugged COM Express (VITA 59 / COM.0)

Computer-On-Modules, -40°C to +85°C Tcase



	 CM50C „The Most Compact One“	 CB71C „The Graphics Monster“	 CB70C „The Multi-Talent“	 CB30C „The Safe One“	 CC10C „The I/O Wonder“
Product Standard	Mini, Type 10	Basic, Type 6	Basic, Type 6	Basic, Type 6	Compact, Type 6
Processor	Intel Atom E3900 series	AMD V1404I, V1807B	Intel Core i7, i5, i3	NXP QorIQ P1022, P1013	NXP ARM i.MX6
Connectivity					
Other I/O	UARTs, GPIO, LPC	UARTs, GPIO	GPIO, SMB, SPI, LPC, speaker	ExpressCard, UARTs, GPIO, I2C, SPI, processor local bus	ExpressCard, CAN bus, UARTs, PWM, GPIO, I2C, SPI
Video/Audio					
RAM max.	8 GB DDR3	32 GB DDR4	16 GB DDR3	2 GB DDR3	4 GB DDR3
Mass Storage	1 × eMMC 2 × SATA 6 Gb - SATA 3 Gb - SDIO	1 × eMMC 2 × SATA 6 Gb - SATA 3 Gb - SDIO	- eMMC 2 × SATA 6 Gb 2 × SATA 3 Gb - SDIO	1 × eMMC - SATA 6 Gb 2 × SATA 3 Gb 1 × SDIO	1 × eMMC - SATA 6 Gb 1 × SATA 3 Gb 1 × SDIO
Power Range	7 W up to 16 W	20 W to 54 W	48 W to 70 W	15 W	5 W to 12 W